



ISO/IEC 19752 Yield Test Report

T640, T642, T644 Print Cartridge

Printer: T640

Part Number: 64015SA 64017SR 64016SE 64018SL
64035SA 64037SR 64036SE 64038SL

Declaration of **Average Cartridge Yield 6000 standard pages**
Yield: **Declared yield value in accordance with ISO/IEC 19752**

Average 7044
Std Dev 358
90% Lower Confidence 6823

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

start 29-Mar-2005 **stop** 1-Apr-2005
Date tested

Number of cartridges in testing 9
Qty. of cartridges used in calculation 9
Shake Procedure 1st shake At toner low
2nd shake At toner low
Print mode Continuous
Number of printers tested 3
Media used Boise Cascade - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version T640 version 1
Operating system Windows 2000
Application software Acrobat version 6.01
Test page version Down load Free__19752 Test Chart.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS050559109	PL2-1034-L	74	24	76	24	72	22	46	53	41	7,160	Yes
CAS050559008	PL2-1037-L	74	24	76	24	72	22	46	53	41	7,000	Yes
CAS050559025	PL2-1037-L	74	24	76	24	72	22	46	53	41	7,200	Yes
CAS050559122	PL2-1034-L	74	24	76	24	72	22	46	53	41	7,260	Yes
CAS050559048	PL2-1037-L	74	24	76	24	72	22	46	53	41	7,500	Yes
CAS050559137	PL2-1026-L	74	24	76	24	72	22	46	53	41	6,700	Yes
CAS050559028	PL2-1026-L	74	24	76	24	72	22	46	53	41	7,439	Yes
CAS050559117	PL2-1026-L	74	24	76	24	72	22	46	53	41	6,620	Yes
CAS050559092	PL2-1034-L	74	24	76	24	72	22	46	53	41	6,520	Yes

Comments and or exceptions: